



□ 回路図 : *CIRCUIT*

□ 外形寸法図 : *OUTLINE DRAWING*



Dimension: [mm]

□ 最大定格 : *MAXIMUM RATINGS* ($T_c = 25^\circ\text{C}$)

Item	Symbol	Rated Value	Unit
コレクタ・エミッタ間電圧 Collector-Emitter Voltage	V_{CES}	1, 200	V
ゲート・エミッタ間電圧 Gate-Emitter Voltage	V_{GES}	± 20	V
コレクタ電流 Collector Current	DC	I_C	300
	1ms	I_{CP}	600
コレクタ損失 Collector Power Dissipation	P_C	1, 460	W
接合温度 Junction Temperature Range	T_j	$-40 \sim +150$	$^\circ\text{C}$
保存温度 Storage Temperature Range	T_{stg}	$-40 \sim +125$	$^\circ\text{C}$
絶縁耐圧(Terminal to Base AC, 1 minute) Isolation Voltage	V_{ISO}	2, 500	$V_{(RMS)}$
締め付けトルク Mounting Torque	Module Base to Heatsink	F_{tor}	3 (30.6)
	Busbar to Main Terminal		
			$\text{N} \cdot \text{m}$ ($\text{kgf} \cdot \text{cm}$)

□ 電気的特性 : *ELECTRICAL CHARACTERISTICS* ($T_c = 25^\circ\text{C}$)

Characteristic	Symbol	Test Condition	Min.	Tvp.	Max.	Unit
コレクタ遮断電流 Collector-Emitter Cut-Off Current	I_{CES}	$V_{CE} = 1200V, V_{GE} = 0V$	—	—	6.0	mA
ゲート漏れ電流 Gate-Emitter Leakage Current	I_{GES}	$V_{GE} = \pm 20V, V_{CE} = 0V$	—	—	1.0	μA
コレクタ・エミッタ間飽和電圧 Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 300A, V_{GE} = 15V$	—	1.9	2.4	V
ゲートしきい値電圧 Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$V_{CE} = 5V, I_C = 300mA$	4.0	—	8.0	V
入力容量 Input Capacitance	C_{ies}	$V_{CE} = 10V, V_{GE} = 0V, f = 1\text{MHz}$	—	25,000	—	pF
スイッチング時間 Switching Time	上昇時間 Rise Time	$V_{CC} = 600V$ $R_L = 2\Omega$ $R_G = 1.3\Omega$ $V_{GE} = \pm 15V$	—	0.25	0.45	μs
	ターンオン時間 Turn-on Time		—	0.40	0.70	
	下降時間 Fall Time		—	0.25	0.35	
	ターンオフ時間 Turn-off Time		—	0.80	1.10	

□ フリーホイーリングダイオードの特性 : *FREE WHEELING DIODE RATINGS & CHARACTERISTICS* ($T_c = 25^\circ\text{C}$)

Item	Symbol	Rated Value	Unit
順電流 Forward Current	DC	I_F	300
	1ms	I_{FM}	600
			A

Characteristic	Symbol	Test Condition	Min.	Tvp.	Max.	Unit
順電圧 Peak Forward Voltage	V_F	$I_F = 300A, V_{GE} = 0V$	—	1.9	2.4	V
逆回復時間 Reverse Recovery Time	t_{rr}	$I_F = 300A, V_{GE} = -10V$ $di/dt = 600A/\mu\text{s}$	—	0.2	0.3	μs

□ 熱的特性 : *THERMAL CHARACTERISTICS*

Characteristic	Symbol	Test Condition	Min.	Tvp.	Max.	Unit
熱抵抗 Thermal Impedance	IGBT	Junction to Case	—	—	0.086	$^\circ\text{C}/\text{W}$
	Diode		—	—	0.16	

Fig.1- Output Characteristics (Typical)




Fig.2- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.3- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.4- Gate Charge vs. Collector to Emitter Voltage (Typical)




Fig.5- Capacitance vs. Collector to Emitter Voltage (Typical)




Fig.6- Collector Current vs. Switching Time (Typical)




Fig.7- Series Gate Impedance vs. Switching Time (Typical)




Fig.8- Forward Characteristics of Free Wheeling Diode (Typical)




Fig.9- Reverse Recovery Characteristics (Typical)




Fig.10- Reverse Bias Safe Operating Area




Fig.11- Transient Thermal Impedance

